



Technical	SAE 20W70 Racing Motor Oil
Product	"Big Daddy" NITRO Service
Information	Formulated with EHP

## PRODUCT DESCRIPTION AND FEATURES

**PurePower! SAE 20W70 Racing Oil** is carefully formulated with a blend of highly refined base oils and specially selected additives designed to provide excellent performance in all Top Fuel and other alcohol-burning racing applications. It contains an effective "state-of-the-art" extreme pressure agent to reduce wear and protect the race engine under the severe demands of Top Fuel competition.

**PurePower! SAE 20W70 Racing Oil** is additionally fortified with oxidation-corrosion inhibitors, high temperature anti-wear additives and foam inhibitors to protect vital engine parts from scuffing and protect bearings from corrosion. It also contains a highly effective detergent-dispersant for maximum engine cleanliness.

## PRODUCT BENEFITS

- Extremely high TBN/Alkaline Reserve – Effectively neutralizes corrosive acids to protect bearings and other vital engine surfaces.
- Proprietary Extreme High Performance (EHP) additive reduces wear and extends engine life.
- EHP Formula provides superior anti-scuff to protect cam lobes and other highly loaded parts from wear.
- High Oxidation Stability protects engine against sludge and varnish deposits.
- Minimized Ash Deposits in combustion chamber and valve surfaces.
- Extremely high load-wear.
- Increased Horsepower.
- Extremely high thermal ability.
- Lower Operating Temperatures.

## PRODUCT APPLICATION

- **PurePower! SAE 20W70 Racing Oil** is engineered specifically for alcohol/nitro fueled racing engines where maximum protection is required for the unique demands of those engines.
- **PurePower! SAE 20W70 Racing Oil** is recommended for use in gasoline and other fuel racing engines when a heavier viscosity racing motore oil is required.
- **PurePower! SAE 10W30 and 15W40 Extreme High Performance Motor Oils** are recommended when outstanding protection for racing engines are required, and a lower viscosity motor oil is preferred.

ASTM D-1298	ASTM D-130	ASTM D-5293		%	ASTM D-2896	ASTM D-1500	ASTM D-9445
Specific Gravity	Corrosion	Viscosity		Sulfur Ash	TBN	Color Amber	Viscosity Index
0.894	1-A	187.69	22.94	.92	13.03	5.0	149

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.  
CHEMISTRY.

THIS PRODUCT CONTAINS ADVANCED HIGH PERFORMANCE ADDITIVE

15751 Chemical Lane, Huntington Beach, CA 92649 Phone: (800) 750-0827 FAX: (714) 894-2994  
[www.purepowerlubricants.com](http://www.purepowerlubricants.com)

©1995 Pure Power! Incorporated.  
Incorporated.

Pure Power!® and Pure Power! Lubricants® are Registered Trademarks of Pure Power!

—

—