



Technical	AUTOMATIC TRANSMISSION FLUID
Product	Formulated with EHP
Information	

PRODUCT DESCRIPTION AND FEATURES

PurePower! Automatic Transmission Fluid is an exceptional ATF that exceeds major U.S. and import car manufacturers' performance requirements.

PurePower! Automatic Transmission Fluid is engineered to exceed DEXRON®III and MERCON® specifications.

PurePower! ATF is formulated with **EHP** to provide extreme film strength to all internal parts. It features an additive package that promotes long transmission life, very low Pour Point, reduced wear, more positive shifting performance and reduced heat.

PRODUCT BENEFITS

- Reduced wear under extreme and normal operating conditions.
- More positive shifting performance.
- Extended automatic transmission life.
- Excellent protection against oxidation and corrosion.
- Exceptional cold weather protection to more than -40°F
- Superior shear and thermal stability, even under severe stress and shock.

PRODUCT APPLICATION

- *PurePower! Automatic Transmission Fluid* is a superior multi-purpose product that can be used for all GM transmissions requiring DEXRON® III fluids, plus transmissions previously requiring DEXRON® II.
- Use for Ford transmissions where MERCON® fluids are specified (usually all automatic transmissions except for Ford M2C33-F (Type F)).
- Recommended for use in Allison automatic transmissions, including Type C-4.
- Recommended for use in Caterpillar transmissions requiring TO-2 specification.
- Specifications may allow application in high speed, high pressure hydraulic equipment, particularly when operated at low ambient temperature.
- May be used in screw type flood-lubricated air compressors, and certain power steering systems (check specifications prior to use).

ASTM D-1298	ASTM D-130	ASTM D-92	ASTM D-92	ASTM D-5293						ASTM D-1500	ASTM D-445	%
Density G/cm ³ @15°C	Corrosion	Fire Point	Flash Point	Viscosity cP@-20°C	cP@-40°C	cSt @ 40°C	cSt @ 100°C	SUS@100°F	SUS@210°F	Color	Viscosity Index	Zinc
0.865	1-A	421°F	392°F	1100	17800	32.3	7.33	163	50.7	Red	203	None

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.
CHEMISTRY.

THIS PRODUCT CONTAINS ADVANCED HIGH PERFORMANCE ADDITIVE

15751 Chemical Lane, Huntington Beach, CA 92649 Phone: (800) 750-0827 FAX: (714) 894-2994
www.purepowerlubricants.com

©1995 Pure Power! Incorporated.
Incorporated.

Pure Power!® and Pure Power! Lubricants® are Registered Trademarks of Pure Power!

DEXRON II®, DEXRON III®, are registered Trademarks of General Motors Corporation and MERCON® is a Registered Trademark of Ford Motor Company.

—

—