



Technical	TransFlush
Product	(for Automatic Transmissions)
Information	

**PRODUCT DESCRIPTION AND FEATURES**

**PurePower! TransFlush** is a highly concentrated formula designed to remove wear debris, dirt, sludge, varnish and acids from automatic transmissions. It is recommended for all automatic transmissions as a flushing agent prior to transmission fluid and filter changes. The one-quart package facilitates cleaning while maintaining ATF fluid viscometrics.

**PurePower! TransFlush** is red in color to identify it as a transmission application. It can also be used as a flush in power steering systems that designate ATF as the lubricant.

**PRODUCT BENEFITS**

- Designed to remove wear debris, dirt, airborne particles, sludge, varnish and acids in automatic transmission.
- Extends the life of the valve body and internal automatic transmission components.
- One-quart application facilitates cleaning while maintaining ATF fluid viscometrics to prevent damage during the cleaning process.

**PRODUCT APPLICATION**

1. Pour entire contents into the automatic transmission.
2. Start the vehicle, and drive for 20 minutes, periodically using all gear selections.
3. Stop engine and allow vehicle to cool for 10 minutes.
4. Drain fluid, change filter, replace gasket.
5. Service with **Pure Power! Automatic Transmission Fluid** with Formula EHP.

**TYPICAL INSPECTIONS**

ASTM D-1298	ASTM D-1298	ASTM D-130	ASTM D-92	ASTM D-5293		ASTM D-1500	ASTM D-445
°API Gravity	Specific Gravity	Corrosion	Flash Point	Viscosity CSt at 40°C - cSt at 100°C		Color	Viscosity Index
33.7	0.857	1-A	>190°F	22.25	5.62	Red	211

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

THIS PRODUCT CONTAINS ADVANCED HIGH PERFORMANCE ADDITIVE CHEMISTRY.